



GENERAL NOTES:

a.) REFER TO BOM LIST WHEN ORDERING PARTS.

b.) REFER TO CARE & OPERATION MANUAL FOR ADDITIONAL INFO.

c.) FACE OF SAE PTO HOUSING TO BOTTOM OF PILOT BORE IN FLYWHEEL.

d.) A SUPPORT PLATE MUST BE USED.

e.) DIMENSIONS WITHOUT TOLERANCES ARE FOR REFERENCE ONLY.

NOTE: SP218P007 IS OBSOLETE FOR PRODUCTION PER ECN11952

NOTICE! THIS PRINT CONTAINS PROPRIETARY INFORMATION AND IS NOT TO BE USED IN ANY MANNER DETRIMENTAL TO THE INTERESTS OF TWIN DISC, INCORPORATED RACINE, WI 53403 - USA THIS NOTICE IS NOT INTENDED TO NULLIFY OR LIMIT RIGHTS GRANTED TO THE U.S. GOVERNMENT OR OTHERS BY CONTRACT.	MATERIAL	WEIGHT	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS <small>MACHINED DIMENSIONS</small> X .015 X .013 X .025 X .013 ALL ANGULAR TOLERANCES ±1° GEOMETRIC TOLERANCING PER ANSI Y14.5M 1982	DATE 2-19-96	
	HEAT TREAT	FIRST USE	SCALE 1:1	DRN. TRL	
	SURFACE TREATMENT	ASSY. MODEL SP218DP0	NAME SP218DP0 P.T.O.	CHK. JMS	APP'D. TRL
				TWIN DISC INCORPORATED RACINE, WI 53403 - USA	
				SP218P001 SP218P003 SP218P004 SP218P005 SP218P007*	
				SHEET 2 OF 2	REV C

F I E D C B A